

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0

Revision Date: 04.01.2012

Superseded date: 15.12.2011

DOW CORNING(R) 730 SOLVENT RESISTANT SEALANT**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY****1.1 Product name** : DOW CORNING(R) 730 SOLVENT RESISTANT SEALANT**1.2 Identified uses** : Corrosion inhibitors
Coatings
Adhesive, binding agents**Uses advised against** : None known.**1.3 Company** : Dow Corning Europe S.A.
rue Jules Bordet - Parc Industriel - Zone C
B-7180 Seneffe
Belgium**E-mail address (Safety Data Sheet)** : sdseu@dowcorning.com**Customer Service** : English Tel: +49 611237507
Deutsch Tel: +49 611237500
Français Tel: +32 64511149
Italiano Tel: +32 64511170
Español Tel: +32 64511163

Fax: +32 64888683

1.4 Emergency Phone Number : Dow Corning (Barry U.K. 24h) Tel: +44 1446732350
Dow Corning (Wiesbaden 24h) Tel: +49 61122158
Dow Corning (Seneffe 24h) Tel: +32 64 888240**2. HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture**

According to EU Directives 67/548/EEC or 1999/45/EC:

R36/38 Irritating to eyes and skin.

2.2 Label elements**Labelling according to EEC Directive****Symbols** : Xi Irritant.**R-phrases** : R36/38 Irritating to eyes and skin.**S-phrases** : S23(S) Do not breathe spray.
S24 Avoid contact with skin.
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37 Wear suitable gloves.
S41 In case of fire and/or explosion do not breathe fumes.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0

Revision Date: 04.01.2012

Superseded date: 15.12.2011

DOW CORNING(R) 730 SOLVENT RESISTANT SEALANT

S51 Use only in well-ventilated areas.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical characterization: Fluorosilicone

According to EU Directives 67/548/EEC or 1999/45/EC:

| Name | CAS-No. | EINECS/ ELINCS No. | REACH Registration Number | Conc. (% w/w) | Classification |
|------------------------|------------|--------------------------|---------------------------------|------------------|---|
| Trimethylated silica | 68909-20-6 | 272-697-1 | - | 7.0 | R66 |
| Triacetoxivinylsilane | 4130-08-9 | 223-943-1 | - | 6.0 | C R34 |
| Dibutyltin di(acetate) | 1067-33-0 | 213-928-8 | - | 0.1 | N C T R50/53 R34 R25 R48/25 T, Toxic for reproduction - category 2. R61 R60 Xn, Mutagen category 3. R68 |

According to Regulation (EC) No. 1272/2008:

| Name | CAS-No. | EINECS/ ELINCS No. | REACH Registration Number | Conc. (% w/w) | Classification |
|------------------------|------------|--------------------------|---------------------------------|------------------|---|
| Trimethylated silica | 68909-20-6 | 272-697-1 | - | 7.0 | Substance with a Community workplace exposure limit |
| Triacetoxivinylsilane | 4130-08-9 | 223-943-1 | - | 6.0 | Skin corrosion/irritation: Category 1B - H314 |
| Dibutyltin di(acetate) | 1067-33-0 | 213-928-8 | - | 0.1 | Acute toxicity (Oral): Category 2 - H300 Skin corrosion/irritation: Category 1B - H314 Germ cell mutagenicity: Category 2 - H341 Reproductive toxicity: Category 1B - H360FD Specific target organ toxicity - repeated exposure (Oral): Category 1 (blood) - H372 Acute aquatic hazard: Category 1 - H400 Chronic aquatic hazard: Category 1 - H410 |

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

CLP classifications are based on all current available data including from known international organizations. These classifications are subject to revision as more information becomes available.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0

Revision Date: 04.01.2012

Superseded date: 15.12.2011

DOW CORNING(R) 730 SOLVENT RESISTANT SEALANT**4. FIRST AID MEASURES****4.1 Description of First Aid Measures:**

- On contact with eyes** : Immediately flush with water. Obtain medical attention immediately.
- On skin contact** : Immediately flush with water. Wipe off. If skin irritation persists, get medical attention.
- If inhaled** : Remove to fresh air.
- On ingestion** : No first aid should be needed.

- 4.2 Most important symptoms/effects, acute and delayed** : Irritating to eyes and skin.

5. FIRE-FIGHTING MEASURES

- 5.1 Suitable extinguishing media** : On large fires use dry chemical, foam or water spray (fog). On small fires use carbon dioxide (CO₂), dry chemical or water spray. Water can be used to cool fire exposed containers.
- Unsuitable extinguishing media** : None known.
- 5.2 Hazards during fire fighting** : Very toxic vapours are evolved.
- Hazardous Combustion Products** : Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde. Very toxic vapours of fluorinated compounds may be formed in trace quantities if the product is heated to 150 °C or above.
- 5.3 Special protective equipment/procedures** : A self-contained respirator and protective clothing should be worn. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures** : Wear proper protective equipment.
- 6.2 Environmental precautions** : Do not allow large quantities to enter drains or surface waters.
- 6.3 Methods and materials for containment and cleaning up** : Scrape up and place in a container fitted with a lid. The spilled product produces an extremely slippery surface.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0
 Revision Date: 04.01.2012
 Superseded date: 15.12.2011

DOW CORNING(R) 730 SOLVENT RESISTANT SEALANT

7. HANDLING AND STORAGE

- 7.1 Advice on safe handling** : General ventilation is required. Local ventilation is required. Avoid skin and eye contact. Do not breathe vapour. Do not breathe spray or mist. Do not empty into drains.
- 7.2 Advice on storage** : Do not store with oxidizing agents. Keep container closed and store away from water or moisture.
 Storage temperature: maximum 32 °C
- 7.3 Specific uses** : Refer to technical data sheet available on request.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

| Name | CAS-No. | Exposure Limits |
|------------------------|-----------|---|
| Dibutyltin di(acetate) | 1067-33-0 | 0.1 mg/m ³ TWA as Sn "organic" 0.2 mg/m ³ STEL as Sn "organic" |

8.2 Exposure controls

Engineering Controls : Ventilation : Refer to Section 7.1

Personal protection equipment

- Respiratory protection** : Suitable respiratory protection should be worn if the product is used in large quantities, confined spaces or in other circumstances where the OEL may be approached or exceeded.
 Depending on the working conditions, wear a respiratory mask with filter(s) EA or use a self-contained respirator.
 The choice of a filter type depends on the amount and type of chemical being handled in the workplace. Regarding filter characteristics, contact your respiratory protection supplier.
- Hand protection** : Chemical protective gloves should be worn: Butyl rubber. Nitrile rubber. Neoprene rubber. Silver shield(TM). 4H(TM). Viton(TM). Regarding glove's breakthrough time, contact your chemical protective glove supplier.
- Eye/face protection** : Face shield or safety goggles.
- Skin protection** : Wear impervious overalls in circumstances where significant skin contact can occur.
- Hygiene measures** : Exercise good industrial hygiene practice. Wash after handling, especially before eating, drinking or smoking.
- Additional information** : These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0

Revision Date: 04.01.2012

Superseded date: 15.12.2011

DOW CORNING(R) 730 SOLVENT RESISTANT SEALANT

Environmental exposure controls : Refer to section 6 and 12.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form : Paste
Colour : White
Odour : Acetic acid
Flash point : > 101.1 °C (Closed Cup)
Explosive properties : No
Specific Gravity : 1.41
Oxidizing properties : No

The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

10. STABILITY AND REACTIVITY

10.1 Reactivity : Cures in the presence of water or moisture, releasing a small amount of acetic acid.
10.2 Stability : Stable under normal usage conditions.
10.3 Possibility of hazardous reactions : None known.
10.4 Conditions to avoid : None established.
10.5 Materials to avoid : Can react with strong oxidising agents. Keep from any possible contact with water. Protect from moisture
10.6 Hazardous decomposition products : Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde. Very toxic vapours of fluorinated compounds may be formed in trace quantities if the product is heated to 150 °C or above.

11. TOXICOLOGICAL INFORMATION**Acute toxicity:**

On contact with eyes : Causes serious eye irritation. Vapour irritates.
On skin contact : Irritating.
If inhaled : The vapour is irritating to the mouth, nose and throat.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0

Revision Date: 04.01.2012

Superseded date: 15.12.2011

DOW CORNING(R) 730 SOLVENT RESISTANT SEALANT

On ingestion : Irritant to mucous membranes.

Chronic toxicity:

On skin contact : Can irritate on prolonged or repeated contact.

If inhaled : Prolonged or repeated inhalation may cause irritation of the upper respiratory system.

On ingestion : Repeated swallowing may cause gastrointestinal irritation and disturbance.

Toxicokinetics, metabolism and distribution : No specific information is available.

Other Health Hazard Information : This product contains (a) powder(s) hazardous by inhalation. This is not relevant to the current physical form of the product, which is not in a respirable form. Product may emit formaldehyde vapour at temperatures above 180°C in the presence of air. Formaldehyde vapour is a suspected carcinogen, toxic by inhalation and irritating to eyes and the respiratory system. Exposure limits should be strictly respected.

¹ Based on product test data.

² Based on test data from similar products.

12. ECOLOGICAL INFORMATION**12.1 Ecotoxicity effects**

No adverse effects on aquatic organisms are predicted.

12.2 Persistence and degradability

Solid material, insoluble in water. No adverse effects are predicted.

12.3 Bioaccumulation

No bioaccumulation potential.

12.4 Release to waters / Mobility in soil**Fate and effects in waste water treatment plants:**

No adverse effects on bacteria are predicted.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0

Revision Date: 04.01.2012

Superseded date: 15.12.2011

DOW CORNING(R) 730 SOLVENT RESISTANT SEALANT**13. DISPOSAL CONSIDERATIONS**

Product and packaging disposal : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

14. TRANSPORT INFORMATION**Road / Rail (ADR/RID)**

UN No. : UN 3261

Proper Shipping Name : CORROSIVE SOLID, ACIDIC, ORGANIC, N.O.S.(Acetoxysilane)

Class : 8

Packing group : III

Labels : 8

Sea transport (IMDG)

UN No. : UN 3261

Proper Shipping Name : CORROSIVE SOLID, ACIDIC, ORGANIC, N.O.S.(Acetoxysilane)

Class : 8

Packing group : III

Emergency Schedule (EmS) : F-A
S-B

Labels : corrosive

Air transport (IATA)

UN No. : UN 3261

Proper Shipping Name : Corrosive solid, acidic, organic, n.o.s.(Acetoxysilane)

Class : 8

Packing group : III

Labels : Corrosive

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0

Revision Date: 04.01.2012

Superseded date: 15.12.2011

DOW CORNING(R) 730 SOLVENT RESISTANT SEALANT**15. REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Status**

TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

EINECS : Not determined.

16. OTHER INFORMATION

This product safety data sheet was prepared in compliance with article 31 and Annex II of the EU REACH Regulation as well as its relevant amendments, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with article 31 and Annex II of the EU REACH Regulation.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.

Source of information: Internal data and publically available information

R25 Toxic if swallowed., **R34** Causes burns., **R48/25** Toxic: danger of serious damage to health by prolonged exposure if swallowed., **R50/53** Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment., **R60** May impair fertility., **R61** May cause harm to the unborn child., **R66** Repeated exposure may cause skin dryness or cracking., **R68** Possible risk of irreversible effects.

H300 Fatal if swallowed., **H314** Causes severe skin burns and eye damage., **H341** Suspected of causing genetic defects., **H360FD** May damage fertility. May damage the unborn child., **H400** Very toxic to aquatic life., **H410** Very toxic to aquatic life with long lasting effects.