

S I L E X

S I L I C O N E S

SILICONE RUBBER VACUUM HOSE - POLYESTER & WIRE REINFORCED (3PLY POLYESTER)

SIZE	I.D	O.D ± 0.6MM	WALL	BEND RADIUS	**WP 20 C BAR	** BP 20 C BAR
½"	12.7mm	22.5mm	4.9mm	75	10	30
¾"	19mm	28.8mm	4.9mm	85	10	30
1"	25.4mm	35.2mm	4.9mm	100	10	30
1 ¼"	31.8mm	41.6mm	4.9mm	120	10	30
1 ½"	38.1mm	47.9mm	4.9mm	145	10	30
2"	50.8mm	60.6mm	4.9mm	250	8	24
2 ½"	63.5mm	73.3mm	4.9mm	300	5	15
3"	76.2mm	86mm	4.9mm	460	3	9
4"	101.6mm	111.4mm	4.9mm	950	3	9

** These are guide figures and should be confirmed by the manufacturer of the Assembly. (Re. fitting design)

** Pressure decrease by 1% for every 1°C, above 100°C.

SILEX LIMITED
UNIT 4 & 5, BROXHEAD TRADING ESTATE, LINDFORD, BORDON, HANTS, GU35 0NY
 TELEPHONE: 01420 487130 / 487538 / 488042 FAX NO: 01420 489274

e-mail (general) info@silex.co.uk Web site: www.silex.co.uk